



Revision Number: 002.0

Issue date: 03/29/2018

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: OSI Quad Advanced Formula Sealant Window, Door & Siding Invisible 000 **IDH number:** 1896952
Product type: Joint sealants
Restriction of Use: None identified **Region:** United States
Company address: **Contact information:**
 Henkel Corporation Telephone: +1 (860) 571-5100
 One Henkel Way MEDICAL EMERGENCY Phone: Poison Control Center
 Rocky Hill, Connecticut 06067 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: FLAMMABLE LIQUID AND VAPOR.
 CAUSES SKIN IRRITATION.
 CAUSES SERIOUS EYE IRRITATION.
 SUSPECTED OF CAUSING CANCER.
 MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	3
SKIN IRRITATION	2
EYE IRRITATION	2A
CARCINOGENICITY	2
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	2

PICTOGRAM(S)



Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use non-sparking tools. Take action to prevent static discharges. Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Wear protective gloves, clothing, eye and face protection.

Response: If on skin (or hair): Take off immediately all contaminated clothing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Xylenes	1330-20-7	10 - 20
Stoddard solvent, <0.1% Benzene	8052-41-3	10 - 20
Ethylbenzene	100-41-4	5 - 10
Naphthalene	91-20-3	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air in case of accidental inhalation of vapours. Administer oxygen or artificial respiration as needed. Get immediate medical attention.
Skin contact:	Rinse with running water. Apply skin care product. Remove contaminated clothes immediately.
Eye contact:	Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.
Ingestion:	Do not induce vomiting. Get immediate medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	carbon dioxide foam Dry chemical. Water spray or fog.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	Closed containers may rupture (due to build up of pressure) when exposed to extreme heat. Vapors are heavier than air and may travel along floor to an ignition source.
Hazardous combustion products:	Oxides of carbon. Carbon dioxide.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Sweep up or gather material and place in appropriate container for disposal. Wash spill area thoroughly. Wear appropriate protective equipment during cleanup. Eliminate ignition sources including sources of electrical, static or frictional sparks.
Clean-up methods:	Not available.

7. HANDLING AND STORAGE

Handling: Keep away from heat, spark and flame. Keep container closed. Do not reuse container. Keep out of the reach of children. Use only with adequate ventilation. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode. Make sure containers are properly grounded before use or transfer of material.

Storage: Keep away from heat, spark and flame.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Xylenes	100 ppm TWA 150 ppm STEL	100 ppm (435 mg/m ³) PEL	None	None
Stoddard solvent, <0.1% Benzene	100 ppm TWA	500 ppm (2,900 mg/m ³) PEL	None	None
Ethylbenzene	20 ppm TWA	100 ppm (435 mg/m ³) PEL	None	None
Naphthalene	10 ppm TWA (SKIN)	10 ppm (50 mg/m ³) PEL	None	None

Engineering controls: Use only in well ventilated areas. Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection: When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection: Wear safety glasses with side shields.

Skin protection: Solvent impermeable gloves are required for repeated or prolonged contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Colorless
Odor:	Slightly, of solvent
Odor threshold:	Not available.
pH:	Not applicable
Vapor pressure:	23 mm hg (20 °C (68°F))
Boiling point/range:	137.8 - 193.3 °C (280°F - 379.9 °F)(solvent)
Melting point/ range:	Not available.
Specific gravity:	0.927
Vapor density:	Heavier than air.
Flash point:	26.67 °C (80.01 °F) no method
Flammable/Explosive limits - lower:	1 %
Flammable/Explosive limits - upper:	7 %
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	35 %; 340 g/l
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Not available.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Carbon dioxide, carbon monoxide and irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.
Incompatible materials:	Strong oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Keep away from open flames, hot surfaces and sources of ignition.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:	Vapors may cause headaches, nausea, dizziness and respiratory tract irritation. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Prolonged exposure to solvents may cause adverse effects to the liver, urinary, and reproductive systems. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release.
Skin contact:	Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitisation of susceptible persons.
Eye contact:	Symptoms can include irritation, redness, scratching of the cornea, and tearing.
Ingestion:	Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Xylenes	Oral LD50 (Mouse) = 1,590 mg/kg Oral LD50 (Rat) = 6,670 mg/kg Oral LD50 (Rat) = 3,523 - 8,600 mg/kg Oral LD50 (Mouse) = 5,627 mg/kg Oral LD50 (Rat) = 4,300 mg/kg Dermal LD50 (Rabbit) = > 43 g/kg Inhalation LC50 (Rat, 4 h) = 6,350 mg/l	Cardiac, Central nervous system, Irritant, Kidney, Liver
Stoddard solvent, <0.1% Benzene	None	Central nervous system, Irritant
Ethylbenzene	Oral LD50 (Rat) = 5.46 g/kg Oral LD50 (Rat) = 3,500 mg/kg Dermal LD50 (Rabbit) = 17,800 mg/kg	Irritant, Central nervous system
Naphthalene	Oral LD50 (Rat) = 490 mg/kg Oral LD50 (Rat) = 2.6 g/kg Oral LD50 (Rat) = 2,200 mg/kg Oral LD50 (Rat) = 2,400 mg/kg Dermal LD50 (Rat) = > 20 g/kg Dermal LD50 (Rabbit) = > 2.0 g/kg	Blood, Central nervous system, Eyes, Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Xylenes	No	No	No
Stoddard solvent, <0.1% Benzene	No	No	No
Ethylbenzene	No	Group 2B	No
Naphthalene	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics Leaching Procedure (TCLP) 40 CFR 261.20-24.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Adhesives
Hazard class or division: 3
Identification number: UN 1133
Packing group: III

International Air Transportation (ICAO/IATA)

Proper shipping name: Adhesives
Hazard class or division: 3
Identification number: UN 1133
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: ADHESIVES
Hazard class or division: 3
Identification number: UN 1133
Packing group: III

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health, Fire

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Xylenes (CAS# 1330-20-7). Ethylbenzene (CAS# 100-41-4). Naphthalene (CAS# 91-20-3).

CERCLA Reportable quantity: Xylenes (CAS# 1330-20-7) 100 lbs. (45.4 kg)
Ethylbenzene (CAS# 100-41-4) 1,000 lbs. (454 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 2, 3, 16

Prepared by: Product Safety and Regulatory Affairs

Issue date: 03/29/2018

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.